

If you have termites, you are racing two clocks. One belongs to the insects quietly carving galleries through your framing. The other belongs to moisture, gravity, and time, all of which exploit weakened wood. Getting solid quotes fast matters, but taking the first estimate seldom ends well. I work with homeowners every season who discover that a “cheap fix” becomes a second project six months later, or that a high bid bundled unnecessary work with the necessary. The aim here is simple: help you compare quotes for termite damage repair near me with a sharp eye, so you hire the right crew at the right price and stop the damage for good.

Why speed and sequencing matter

Termites do not stop on their own. Even after treatment, existing damage remains and can worsen under load or with leaks. Good sequencing reduces risk: identify active infestation, treat, verify control, then complete termite damage restoration. Skipping steps causes callbacks. I have seen homes that replaced drywall before confirming moisture and control, only to open walls twice and triple their cost.

In most areas, a licensed pest control company handles elimination, and a separate contractor performs termite repair services. Some firms do both, but quotes should still list treatment and repair as distinct scopes. This separation lets you compare apples to apples.

Quick signs you need repair, not just treatment

- Floors that bounce or feel uneven, especially along walls and under bathrooms.
- Doors or windows racking out of square after a wet season or a plumbing leak.
- Baseboards that crumble at touch, blistered paint, or mud tubes reappearing after spot treatment.
- A sagging porch beam, cracked interior corners, or stair risers separating.
- Hollow-sounding trim or sills near planters, downspouts, or irrigation.

When these show up, you are looking at termite wood repair, not only extermination. Expect wall and floor openings, partial reframing, and finish restoration.

What builds the price of termite repair

Every quote rolls up the same ingredients: scope, access, materials, labor, safety, and risk. Ask each contractor to itemize:

- Scope: Which members get replaced, sistered, or reinforced. Termite structural repair versus cosmetic termite drywall repair after termite treatment.
- Access: Crawlspace versus slab, finished basement ceilings, tiled baths, tight attics.
- Materials: Species, grades, and treatments. Pressure treated bottom plates, borate-treated lumber for framing repair inside conditioned space, engineered LVL or steel for beams when spans demand it.
- Labor and shoring: Temporary supports, jacks, cribbing, demolition, and reconstruction.
- Moisture corrections: Leaky hose bibbs, flashing, grade problems, bath vent rerouting.
- Finish work: Drywall, paint, trim, flooring patching or replacement.
- Permits and engineering: Required when moving or replacing load-bearing elements.
- Warranty: On workmanship, materials, and whether it transfers if you sell.

Two quotes that look far apart often differ because one includes shoring and permits and the other does not. A fair comparison levels those line items.

Active infestation versus dead damage


Repair contractors should not guess at active termites. Ask for a current WDI or WDO inspection report from a licensed pest professional. If treatment is still needed, schedule that first. Some contractors coordinate with your pest provider to open targeted areas so the applicator can treat concealed galleries in studs, sills, or rim joists. After treatment, leave enough time to confirm control, typically a week or two depending on the method, then start repairs. Termite repair near me searches often turn up firms that promise both in a day. Be cautious. Good outcomes follow order.

Understanding specific repairs, piece by piece

Termites do not damage everything evenly. Knowing common assemblies helps you read quotes intelligently.

Termite sill plate repair

The sill plate sits on the foundation and carries wall loads. Subterranean termites love this member, especially where exterior grade is too high or sprinklers hit the wall. Sill plate replacement involves supporting the wall above with temporary posts, then removing sections and installing new pressure treated plates with proper anchors and sill seal. Expect careful sequencing so loads transfer safely. In many jurisdictions, this triggers a permit, and if long runs are affected, an engineer may specify splice details. Typical costs range from a short 6 to 8 foot section around 1,500 to 2,500 dollars to long runs spanning multiple rooms that can land between 4,000 and 8,000 dollars, more if masonry work is needed due to rot.



Termite floor joist repair

Bouncy floors, cracked grout, and doors rubbing can signal joist damage. Joist sistering means fastening a new full-length or partial-length joist alongside the damaged one, bearing properly on supports. When decay is extensive, full replacement may be required. Access drives cost here: a tight crawlspace adds hours, and removing finished ceilings below adds days. I typically see 400 to 800 dollars per joist for sistering in good access, with full replacements, ceiling demo, and finish repair pushing individual joists to 1,200 dollars or more.

Termite beam repair

Main beams carry heavy loads. Evidence of crushed fibers, shear cracks at supports, or visible galleries demands urgency. Structural termite repair near me often specifies engineered LVL sisters or steel flitch plates bolted to the beam, and temporary shoring while work proceeds. Beams intersect with utilities, so expect coordination to reroute or temporarily disconnect lines. Project costs vary wildly, but a modest beam reinforcement might run 2,500 to 5,000 dollars, while replacing a long interior beam can climb past 10,000 dollars with engineering and finishes.

Termite subfloor repair

Subfloor soft spots, cupping, or spongy feel near kitchens and baths typically combine moisture and termites. Subfloor repair requires removing finish flooring, cutting back to joist centers, and installing new panels with proper adhesive and fasteners. Match thickness and grade, and stagger seams. One room of termite subfloor repair commonly falls between 1,200 and 3,000 dollars before flooring replacement.

Termite wall repair and framing repair

Studs, bottom plates, and headers can all be affected. Repairs range from dropping in sister studs to reconstructing entire wall sections. Windows and doors might need new jack and king studs to restore plumb and bearing. Where exterior sheathing and siding show damage, quotes should include weather-resistive barrier replacement, flashing, and siding patching. Interior loads near stairs or chimneys add complexity and often a quick engineer review.

Termite attic wood repair

In attics, termites follow moisture and warmth from bathrooms, chimneys, and poorly vented spaces. Rafters, collar ties, and ridge boards may need sisters or plates. Roof loads are unforgiving, so shoring and careful workmanship prevent sag or ripple telegraphing through shingles. The contractor's safety plan matters here, especially if the attic has loose-fill insulation and HVAC equipment that limits movement.

Drywall repair after termite treatment

After termite treatment and framing fixes, walls need closing. Termite drywall repair after termite treatment involves straightening studs, installing new boards, taping, and matching texture. Painters with a steady hand can blend patches invisibly, but allow for primer designed to block tannins and any staining from old infestations. Expect 300 to 900 dollars per room depending on patch sizes, texture, and paint quality.

How to compare competing quotes, fairly and fast

Here is the simple, repeatable method I use with homeowners deciding among local termite damage repair bids:

- Ask all bidders to write the same scope narrative, including treatment status, targeted members, shoring approach, and finish restoration. No vague "repair termite damage to house."
- Request a line-item breakdown for labor, materials, permits, engineering, disposal, and allowances for hidden conditions.
- Confirm material specs in writing: species, pressure treated versus borate treated, fastener types, connectors, and any beam size or LVL ratings.
- Verify schedule and sequencing, including how long shoring stays, who handles moisture corrections, and whether they coordinate with your pest company.

- Compare warranties side by side, workmanship length, transferability, and exclusions such as moisture recurrence or preexisting plumbing leaks.

With those five pieces, you can justify picking something other than the lowest number because you are choosing the best coverage and risk profile.

Local versus out-of-area crews

Searching termite damage repair near me or wood repair contractor termite damage near me usually turns up a mix of specialists and general carpenters. Local termite damage repair teams tend to know the soil conditions, building codes, and the usual hiding places for infestations in your housing stock, which saves exploratory demolition. Out-of-area outfits may be fine for simple cosmetic work, but when you need termite structural repair, a crew that has patched a hundred crawlspaces in your ZIP code works faster and leaves fewer mysteries behind.

Ask for two local references with similar repairs, ideally within the last year. Call them. The right contractor welcomes that.

Permits, engineering, and when you truly need them

Not every repair requires a permit. Replacing a handful of studs or a small subfloor patch often falls under minor repairs. As soon as you touch a load-bearing member, alter a beam, or replace significant lengths of sill plate, most jurisdictions require permits and, sometimes, stamped drawings or a letter from a structural engineer. Good contractors know the threshold and will not gamble with your house.

Engineering adds cost, usually 400 to 1,200 dollars for a site visit and a letter or light sketch. It also gives you a document to show buyers later, which can pay you back when it is time to sell. Quotes that skip this when it is obviously needed are not bargains. They are liabilities.

Temporary shoring is not optional

Any quote for termite beam repair or heavy framing work should describe shoring. Look for hydraulic jacks on solid cribbing, screw jacks rated for the load, and gradual lifts measured in small increments to avoid cracking finishes or doors binding. I once walked a project where a handyman used stacked bricks as temporary supports. It cost the owner a bathroom tile job when the stack shifted. Ask the contractor to show you their shoring gear and explain the sequence.

Materials and methods that actually last

A few choices separate quick fixes from durable repairs:

- Pressure treated lumber for bottom plates and any wood in contact with concrete or masonry.
- Borate-treated dimensional lumber for interior framing where moisture is controlled, especially effective as part of termite damage restoration because borates deter future activity.
- Proper fasteners and connectors rated for contact with treated lumber. Standard bright nails corrode against treated chemicals.
- Full bearing for sisters. A 10 foot sister that floats 2 inches off a sill is a cosmetic brace, not structural.
- Sealants and flashing that divert water, because moisture drives termites and decay in tandem.

If a contractor waves away these details, keep interviewing.

Moisture corrections, the unglamorous fix that saves money

I rarely see termites without moisture. Irrigation that hits siding, negative grade toward the house, leaky pans under tubs, dryer vents dumping into crawlspaces, bath fans vented to attics, all of these set the stage. Build time into your plan for downspout extensions, regrading, proper bath fan ducting, and a quick plumbing check. The cheapest termite repair services are the ones you never need again.

Realistic cost ranges and what affects them

Home size, access, and finishes push costs around. Across my projects and colleagues' notes, homeowners typically spend:

- 800 to 3,000 dollars for treatment only, separate from repairs, depending on method and foundation.
- 1,500 to 5,000 dollars for termite sill plate repair along a side of the house.
- 400 to 800 dollars per joist for sistering with reasonable access, 1,200 dollars or more if ceilings come down.
- 2,500 to 10,000 dollars for termite beam repair, depending on span, species, and finish impacts.
- 1,200 to 3,000 dollars per room for termite subfloor repair, excluding new flooring.
- 300 to 900 dollars per room for termite drywall repair after termite treatment.

Permits run 75 to 300 dollars in many towns. Dump fees and disposal add a few hundred. These numbers are not promises, they are anchors for your comparisons.

Timing: how long you will live with the mess

Once treatment is confirmed, small framing repairs and wall patches sometimes wrap in 2 to 4 days. Multi-room sill plate and joist work can run 1 to 2 weeks, longer with engineering, inspections, and finish carpentry. Factor dry times for compounds, primers, and any flooring adhesives. A crew that quotes half the days of another should explain their labor plan. Speed is good until it outruns inspection schedules or safe shoring.

Insurance, warranties, and resale

Homeowners insurance rarely covers termite damage because it is considered preventable maintenance. There are exceptions, for example when a covered water loss coincides with or reveals termites. Read your policy and call your agent before work starts. Some pest companies offer retreatment warranties, which do not include repairs. Clarify in writing what the contractor's warranty covers. When you sell, buyers and inspectors will ask about termite repair near me history. A clean packet with treatment reports, permits, and invoices is worth real money.

Red flags in termite damage contractor near me searches

I keep a short mental list of red flags collected from projects that went sideways:

- The contractor will not open exploratory areas before committing to a price but refuses to add a hidden-conditions allowance.
- They promise structural fixes without shoring, or they cannot describe their shoring plan.

- They bundle treatment and repair but cannot provide a pest license number, chemical labels, or a WDI report.
- No mention of permits for major structural work, or pressure to “keep it off the city’s radar.”
- A bid that is dramatically lower but swaps specified materials for generic “treated wood” without fastener compatibility or product data.

A strong contractor expects good questions and answers them plainly.

After the repairs: prevention that actually works

Termites return to friendly environments. Keep things unfriendly. Maintain a clear 6 to 8 inch gap between soil and siding. Move firewood away from the foundation. Divert sprinklers off the house. Ventilate crawlspaces according to your climate’s practice, and consider a proper vapor barrier over soil. Schedule annual inspections, even if you see nothing. In my area, a quick yearly look costs less than replacing a single stud, and it has saved more than one client from a second round of termite structural repair near me.

A short example from the field

A couple called after discovering soft baseboards along a dining wall. The first quote said to replace drywall and baseboards for 1,400 dollars. No mention of treatment or framing. We opened a 2 foot section below the window and found eaten studs, a chewed sill plate, and irrigation spray hitting the wall every morning. The adjusted plan: treat, reroute the sprinkler head, replace 10 feet of sill plate with pressure treated lumber, add two sister studs and a new jack under the window, install flashing, then close with new drywall and paint. Two permits, one quick engineer letter for the window header splice, and a bill of 4,900 dollars. Not cheap, but the house stood straighter, and the problem did not return. That is the difference between cosmetic and structural thinking.

Bringing it all together

Comparing quotes for termite damage repair near me is not about hunting the lowest total. It is about understanding scope, materials, access, risk, and sequencing so you can line up bids that actually match. Ask for clear narratives that describe termite wall repair, termite floor joist repair, termite sill plate repair, termite beam repair, termite subfloor repair, and any termite attic wood repair. Insist on written specs. Confirm treatment status before finish work. Weigh warranties and the contractor’s plan for permits and shoring. Favor local termite damage repair experience when framing is involved, and keep moisture control front and center.

Do that, and you will choose a contractor who repairs termite damage to house safely, restores the structure cleanly, and gives you a folder of documents you can hand to the next owner with confidence. Your walls will be square, your floors steady, and the termites out of luck.